



DETAIL A

SECTION A-A

DETAIL B

LEGEND	
	WHITE LINE
	YELLOW LINE

* = LATERAL DEVIATION SHALL NOT EXCEED ONE INCH IN 100 FEET.

- (1) OFFSET FROM EDGE OF TRAVELED WAY (TYP.)
- (2) OFFSET FROM JOINT (TYP.)
- (3) OFFSET FROM CENTERLINE (TYP.)

GENERAL NOTES:

CENTERLINE RUMBLE STRIPS ON PASSING ROADWAYS SHALL FOLLOW PAVEMENT STRIPING THROUGH TRANSITIONS. SEE CONTRACT PLANS FOR STRIPING DETAILS.

RUMBLE STRIPS SHALL NOT BE PLACED ON BRIDGES.

ALL RUMBLE STRIPS SHALL BE MILLED.

CENTERLINE RUMBLE STRIPS SHALL BE CONTINUOUS THROUGH CONNECTIONS OF SIDEROADS WITH NO LEFT TURN LANES.

DISCONTINUE CENTERLINE RUMBLE STRIPS THROUGH THE LIMITS OF ALL LEFT TURN LANES, INCLUDING ANY LANE TAPER SECTIONS.

RUMBLE STRIP

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

PASSING LANE RUMBLE STRIP AND PAVEMENT MARKING

DATE: _____

EFFECTIVE: XX-01-2007

SPECIAL SHEET

1

1