

Work Zone Calculated Capacity for 3 lanes/1 lane open

Climbing Grade (%)	Length (mi)	2	4	5	6	8	10	15	20	25	30	35	40
<2		960	960	960	960	960	960	960	960	960	960	960	960
>2-3	0 - 0.49	960	960	960	960	960	960	960	960	960	960	960	960
	0.5 - 0.74	960	960	960	960	960	960	960	960	960	960	960	960
	0.75 - 1.00	960	960	960	960	960	960	960	960	960	960	960	960
	>1.00	960	960	960	960	960	960	960	960	960	960	960	960
>3-4	0 - 0.49	960	960	960	960	960	960	960	960	960	960	960	960
	0.5 - 0.74	960	960	960	960	960	960	960	960	960	960	960	960
	0.75 - 1.00	960	960	960	960	960	960	960	960	960	960	960	960
	>1.00	960	960	960	960	960	960	960	960	960	960	960	960
>4-5	0 - 0.49	960	960	960	960	960	960	960	960	960	960	960	960
	0.5 - 0.74	960	960	960	960	960	960	960	960	960	960	960	960
	0.75 - 1.00	960	960	960	960	960	960	960	960	960	960	941	889
	>1.00	960	960	960	960	960	960	960	960	960	960	941	889
>5-6	0 - 0.49	960	960	960	960	960	960	960	960	960	960	960	960
	0.5 - 0.74	960	960	960	960	960	960	960	960	960	960	941	889
	0.75 - 1.00	960	960	960	960	960	960	960	960	960	960	941	889
	>1.00	960	960	960	960	960	960	960	960	985	914	853	800
>6	0 - 0.49	960	960	960	960	960	960	960	960	960	960	960	960
	0.5 - 0.74	960	960	960	960	960	960	960	960	960	960	941	889
	0.75 - 1.00	960	960	960	960	960	960	960	960	960	914	853	800
	>1.00	960	960	960	960	960	960	960	960	914	842	780	727