



DETAIN II ®

DEPOSITION AID / DRIFT RETARDANT

PRINCIPLE FUNCTIONING AGENTS:

Polyacrylamide Copolymer 30	%
Inert Ingredients	%
TOTAL 100	%

The principle functioning agents are exempt from tolerance requirements under Title 40, Code of Federal Regulations 180.1001 (d).

CAUTION

KEEP OUT OF REACH OF CHILDREN

May cause irritation to skin and eyes. If in contact, flush immediately with plenty of water. See a doctor if irritation persists. Follow appropriate precautions on label of pesticide used.

SHAKE WELL BEFORE USING

GENERAL INFORMATION

DETAIN II is an effective, easy to use adjuvant for deposition improvement and drift retardation in spraying operations.

SPRAY PRESSURE	NOZZLE ORIENTATION	<u>DETAIN II DOSAGE</u>
Aerial Applied:		
below 45 psi	Straight Back	14-20 oz. / 100 gal.
	45° Angle Back	16-24 oz. / 100 gal.

Ground Applied:

nound Applica.		FG1 #387855
20-40 psi	Flat Fan	4-8 oz. / 100 gal 12-16 oz. / 100 gal.
20-50 psi	Off-Center	12-16 oz. / 100 gal.
50-150 psi	Brush Gun	32-64 oz. / 100 gal.
20-40 psi	Direct Spray	16-32 oz. / 100 gal.

For home and garden sprayers, use approximately 1 tablespoon of **DETAIN II** per 5 gallons of spray solution.

DIRECTIONS FOR USE

IMPORTANT: Keep container closed in storage and do not allow water to come in contact with contents until added to the spray solution. In case of contact with skin or eyes, flush immediately with plenty of water.

- Step 1. Select correct dosage from chart.
- Step 2. Fill mix tank with water, pesticide and other additives and begin to agitate.
- Step 3. SHAKE BOTTLE OF **DETAIN II** WELL BEFORE USING.
- Step 4. For best mixing results, either (1) inject **DETAIN II** liquid into the suction side of the feeder or recirculating pump to obtain adequate dispersion of the polymer throughout the pesticide solution, or (2) slowly add **DETAIN II** liquid to the rapidly agitating tank mix in the area of highest turbulence by pouring a thin stream.
- Step 5. Continue to agitate tank mix for at least 2 minutes before spraying.
- Step 6. Follow all cleanup precautions on label of pesticide used. Follow governmental procedures for disposal of pesticide spray solution.

USE PRECAUTIONS

The degree of drift hazard varies with the type of pesticide, application conditions, and vegetation near the sprayed area. Remember, pesticide drift is no accident. Common sense and sound application technology must be followed when spraying pesticides. **DETAIN II** will retard, but not totally eliminate drift.

STORAGE AND DISPOSAL

Protect from freezing. Freezing may cause separation. Do not contaminate water, food, or feed by storage or disposal. Keep container tightly sealed when not in use. Do not reuse container. Triple rinse (or equivalent) and then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities, burning. If burned stay our of smoke.

NOTICE-READ CAREFULLY

Conditions of Sale: Estes, Inc. (and seller) offer(s) this product for sale subject to buyer and all users are deemed to have accepted the following conditions of sale and warranty.

Warranty Limitation: Estes, Inc. warrants that this product conforms to the chemical description on the label subject to the inherent risks referred to below. Estes, Inc. makes no other express warranties. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY and there are no warranties which extend beyond the description of label hereof.

Inherent Risks: The directions for use of this product are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks associated with use. Buyer assumes all risks associated with use of application of the product contrary to label instructions or resulting from extraordinary weather conditions. Limitation of Liability: In no case shall Estes, Inc. be liable for special, indirect or consequential damages resulting from the use or handling of this product and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which such damages are claimed.

Manufactured for: Estes, Inc., Wichita Falls, TX 76301

DETAIN II is a registered trademark of Estes, Inc.

